

## CL1200 Electronic Cabinet Lock

### CL1200 Electronic Cabinet Lock

The Cabinet Lock can be fitted to:

- A) Cabinets, cupboards and lockers etc as a direct replacement for existing cam locks.
- B) It can also be fitted to cupboards and cabinets that do not have an existing locking device

#### Special Notes

- Before installing the lock, load the batteries and familiarise yourself with the operation and programming.
- The handle will not turn until you enter the factory default Master Code 11 33 55 77 OR the User Code 22 44.
- Please see the programming guide to now set your new Master and User Codes and to set different functions on lock if required.

#### Installation Guide

##### A) Replacing existing cam lock with the Cabinet Lock

1. Remove existing cam lock.
2. Place template over hole left by cam lock and mark upper fixing hole.
3. Drill the two 6mm fixing holes.
4. Fit lock to door with gasket in place using fixing bolts. Cut bolts to correct length. Measured from beneath the bolt head, the length should be the cabinet thickness, plus approx 12mm.
5. From the inside of the door select and fit appropriate cam spindle and cam using cam fixing bolt supplied. The length of cam and spindle selected to suit your door and frame.
6. Before closing the door check the operation of the lock with Master and User Code.
7. If not changed already CHANGE FACTORY SET MASTER AND USER CODE NOW!

##### B) New installation

1. Place template on door and mark upper and lower 6mm fixing holes and 16mm spindle hole.

- Important note:** Before drilling fixing holes, please ensure that the position of the Cabinet Lock when fitted will allow enough clearance for selected cam to work.
2. Drill all three fixing holes.
  3. Continue installation from step 4 to 7, above.

